

Everest 3DE

Flexible, safe and inexpensive: the perfect solution for accessing great heights.

Product description

- Convenient and precise rung-by-rung height adjustment in increments of 280 mm.
- Upper ladder can be used separately as a single ladder (no. 44851 and 44852).
- Overall width of bottom section: 490 mm.
- Sturdy triangular rungs made from extruded profiles that have a horizontal stepping surface when in the use position.
- Stiles made from extruded aluminium sections for maximum stability.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.



Product features

Coating: natural
 Connection between stiles and rungs/stiles: flanged
 External width of lower ladder: 490 mm
 Load: max. 150 kg
 Material: aluminium
 Product type: Flanged push-up ladder with rungs, 3 sections
 Tread depth: 38 mm
 Type of rungs/treads: serrated
 Vertical distance between each rung/tread: 265 mm

Hints and special features

Complies with EN 131 Professional.

Product variants

Order number	Number of rungs	Number of rungs	Overall length, extended	Overall length, retracted	Stile depth	Transport dimensions	Weight	Wide crosspiece	Working height
44851	8	3 × 8	5.25 m	2.41 m	68 mm	2.410 mm × 500 mm × 170 mm	15.3 kg	0.9 m	5.95 m
44852	10	3 × 10	6.65 m	2.97 m	73 mm	2.970 mm × 500 mm × 190 mm	19.2 kg	1.1 m	7.25 m
44853	12	3 × 12	8.33 m	3.53 m	85 mm	3.530 mm × 500 mm × 190 mm	24.2 kg	1.2 m	8.8 m
44854	14	3 × 14	9.45 m	4.09 m	85 mm	4.090 mm × 500 mm × 190 mm	36 kg	1.2 m	9.9 m