

QUATRO QTV

Small size and huge help

QuickTruss® M290V



The M290 system is the mid-size truss line offered in the QuickTruss® family.

QuickTruss® M290V fits nicely in both large and small applications. Available in heavy-duty "V" Range format, it offers great spanning and weight loading capabilities while providing a decorative touch! M290V is perfect for larger spans up to 16 meters (52.5").

The connection method is the same Conical Connection system used in the M222 Series, just larger in size. QuickTruss® M290V is available in custom lengths and junctions, and can be curved (See Circle Section). It comes in Natural Silver or a wide variety of Powder Coated colors and finishes.



tubes	48 x 3 mm	1 7/8" x 1/8"	braces	16 x 2 mm	5/8" x 1/12"	alloy	EN - AW 6082 T6
-------	-----------	---------------	--------	-----------	--------------	-------	-----------------

QUATRO M290V														
Span in m (ft)	4,00	13.12	6,00	19.69	8,00	26.25	10,00	32.81	12,00	39.37	14,00	45.93	16,00	52.50
point load in kg (lbs)	1464,00	3227.56	964,00	2125.25	710,00	1565.28	555,00	1223.56	449,00	989.87	371,00	817.91	311,00	685.64
deflection in mm (inch)	11,00	0.43	25,00	0.98	45,00	1.76	71,00	2.77	102,00	3.98	140,00	5.46	185,00	7.22
two point load in kg (lbs)	849,00	1871.72	723,00	1593.94	532,00	1172.86	416,00	917.12	337,00	742.96	278,00	612.88	233,00	513.68
deflection in mm (inch)	11,00	0.43	32,00	1.25	57,00	2.22	89,00	3.47	128,00	4.99	174,00	6.79	227,00	8.85
distrib. loading in kg/m (lbs/ft)	425,00	285.56	281,00	188.80	177,00	118.93	111,00	74.58	75,00	50.39	53,00	35.61	39,00	26.20
total distrib. loading in kg (lbs)	1700,00	3747.85	1686,00	3716.99	1416,00	3121.74	1110,00	2447.13	900,00	1984.16	742,00	1635.83	624,00	1375.68
deflection in mm (inch)	8,00	0.31	27,00	1.05	56,00	2.18	87,00	3.39	125,00	4.88	170,00	6.63	222,00	8.66

metric data	imperial data	point load in kg (lbs)	two point load in kg (lbs)	distrib. load (UDL) in kg/m (lbs/ft)
-------------	---------------	------------------------	----------------------------	--------------------------------------

STANDARD LENGTHS AVAILABLE AND WEIGHTS

m (ft)	0,50	1.64	1,00	3.28	1,50	4.92	2,00	6.56	2,50	8.20	3,00	9.84	4,00	13.12	5,00	16.41
Quatro-kg (lbs)	3,20	7.05	8,00	17.64	11,50	25.35	12,80	28.22	16,00	35.27	19,20	42.33	25,60	56.44	32,00	70.55

connection material (pins/clips/cone) and packaging not included in above weights

To view all parts & accessories on line please click [here](#)