PROFESSIONAL RANGE







Litebeam MK II is a lightweight trussing system providing a quick but structurally powerful solution to most exhibition and smaller presentation requirements.

Manufactured using 6082 -T6 aluminium alloy Litebeam MK II is quick and easy to assemble using Slick's unique taper fitting system. This forms a neat and rigid joint and combines with the high quality alloy to provide the truss with an exceptional load capacity for its size.

Coupled with Liteladder and Litemast, Litebeam MK II can be configured to satisfy a wide range of demands in almost every market to which it can be applied, deceptively strong, this system has been used successfully in night-clubs, theatres, exhibitions, corporate presentations and tours.

Litebeam MK II comes in lengths from 0.25m to 6m with Male taper fittings at one end and Female the other.

Corners are supplied with Female fittings and Female to Male adapters, this significantly reduces the number of corners required to configure truss to the required design.

Liteladder and Litemast adapters are available to add extra design opportunities to the system.

Litebeam MK II can be supplied in a variety of powdercoated finishes and circles can be made to your specification.

	Span	Span	Distributed Load	Distributed Load	Deflection	Central Point Load	Central Single Load	Deflection	3rd Point Load	3rd Point Load	Deflection	Qtr Point Load	Qtr Point Load	Deflection	5th Point Load	5th Point Load	Deflection
	m	ft	kg	lbs	cm	kg	lbs	cm	kg	lbs	cm	kg	lbs	cm	kg	lb	cm
	1.00	3,3	1697.3	3734,1	0,1	1526,4	3368,7	0,1	848,6	1872,9	0,1	565,2	1247,3	0,1	424,3	936,5	0,1
	2.00	6,6	1521,2	2939,6	0,3	760,6	1678,5	0,2	570,4	1258,9	0,3	380,3	839,3	0,3	315,6	696,6	0,3
	3.00	9,8	1008,3	2218,3	0,6	504,1	1112,6	0,5	378,1	834,4	0,6	252,1	556,3	0,6	209,2	461,7	0,6
	4.00	13,1	750,0	1650,0	1,1	375,0	827,7	0,9	281,3	620,8	1,1	187,5	413,8	1,0	155,6	343,5	1,1
	5.00	16,4	593,5	1305,7	1,7	296,9	655,2	1,4	222,7	491,4	1,7	148,4	327,6	1,6	123,2	271,9	1,7
	6.00	19,7	488,4	1074,5	2,5	244,2	538,9	2,0	183,1	404,2	2,5	122,1	269,5	2,3	101,3	223,6	2,5
	7.00	23,0	412,3	907,1	3,36	206,1	454,8	2,7	154,5	341,1	3,4	103,0	227,4	3,2	85,5	188,7	3,4
2	8.00	26,2	354,4	779,7	4,4	177,0	390,7	3,5	132,8	293,0	4,5	88,5	195,3	4,1	73,5	162,1	4,5
1	9.00	29,5	307,8	677,2	5,5	154,0	340,0	4,4	115,5	255,0	5,7	77,0	170,0	5,3	63,9	141,1	5,7
	10.00	32,8	271,0	596,2	6,8	135,3	298,6	5,5	101,5	224,0	7,0	67,7	149,3	6,5	56,2	123,9	7,0
	11.00	36,1	240,0	528,0	8,3	119,7	264,1	6,6	89,8	198,1	8,4	59,8	132,1	7,8	49,7	109,6	8,4
1	12.00	39,4	212,4	467,3	9,8	106,3	234,7	7,9	79,8	176,0	10,0	53,2	117,3	9,3	44,1	97,4	10,0



All Slick Truss is designed and calculated to the following standards: DIN 1055, DIN 18800, DIN 4112, DIN 4113, DIN 1481.

All Slick Truss conforms to the "U-sign" for quality conformance.

Slick (UK) Ltd is quality controlled internally to EN 729-3 and 729-4 and externally by the RWTUV, Essen and to EN4113-1.

All of our welders are certified to EN287-2.

HORIZONTAL CORNER BLOCKS

NOTE: Imperial lengths and weights are approximate. (Mt x 39.36 = ins)



HORIZONTAL/VERTICAL CORNER BLOCKS

NOTE: Imperial lengths and weights are approximate. (Mt x 39.36 = ins)





HORIZONTAL/VERTICAL CORNERS

456

NOTE: Imperial lengths and weights are approximate. (Mt x 39.36 = ins)

SWIVEL CORNERS



LBSH/H SWIVEL HINGE HORIZONTAL 8.5kg (18.7lbs)



LB8/VU

LITE BEAM STRAIGHT WITH

ONE EXTRA FACE UP

5.2kg (11.4lbs)

LB9/ATP/A 90 dg CORNER BLOCK WITH ONE EXTRA FACE DOWN AND UP - RIGHT HAND 6 Kg (13.2lbs)



LB9/VU

3 WAYCORNER BLOCK WITH ONE

EXTRA FACE UP

456

LB10VD 4 WAY CORNER BLOCK WITH ONE EXTRA FACE DOWN 7.2kg (15.8lbs)



LB9/ATP/B 90 dg CORNER BLOCK WITH ONE EXTRA FACE DOWN AND UP - LEFT HAND 6 Kg (13.2lbs)



LB9/VD 3 WAY CORNER BLOCK WITH ONE EXTRA FACE DOWN 5.7Kg (12.5lbs)



LB10/VDU 4 WAY CORNER BLOCK WITH ONE EXTRA FACE DOWN 8.4 (18.5lbs)





HEAD & BASE PLATES



STEEL BASE PLATE, 50CM SQUARE MALE



STB/F STEEL BASE PLATE 50CM SQUARE FEMALE



STB/A/T/M ALUMINIUM TRIANGULAR BASE PLATE MALE



STB/A/T/F ALUMINIUM TRIANGULAR BASE PLATE FEMALE



LBTP/M 30CM SQUARE ALUMINIUM PLATE MALE



LBTP/C HEAD PLATE WITH U CLAMPS FEMALE

SLICK	LITE BEAM TRUSS LENGTHS
LB250	0.25Mt Truss Section
LB500	0.5Mt Truss Section
LB626	0.626Mt Truss Section
	(Equivalent Length to an LB8 Corner)
LB1000	1.0Mt Truss Section
LB1500	1.5Mt Truss Section
LB2000	2.0Mt Truss Section
LB2500	2.5Mt Truss Section
LB3000	3.0Mt Truss Section
LB3500	3.5Mt Truss Section
LB4000	4.0Mt Truss Section
LB4500	4.5Mt Truss Section
LB5000	5.0Mt Truss Section
LB5500	5.5Mt Truss Section
LB6000	6.0Mt Truss Section
SLICK	LITE BEAM HORIZONTAL CORNERS
LB5	90dg Corner Block
LB9	3 Way Corner Block
LB10	Four Way Corner Block
LB11	60dg Corner Block
LB13	45dg Corner Block
LB135	135dg Corner Block
SLICK	LITE BEAM HORIZONTAL/VERTICAL CORNERS
LB5/VD/A	90dg Corner Block + Face Down/L-Hand
LB5/VDU/A	90dg Corner Block + Face Down + Face Up/
	L-Hand
LB5/VU/A	90dg Corner Block + Face Up/L-Hand
LB5/VD/B	90dg Corner Block + Face Down /R-Hand
LB5/VDU/B	90dg Corner Block + Face Down + Face Up/R-
Hand	
LB5/VU/B	90dg Corner Block + Face Up/R-Hand
LB6/A	90dg Corner Block With Tower Plate/L-Hand
LB6/B	90dg Corner Block With Tower Plate/R-Hand
LB7	90dg Goal Post Corner
LB7/INV	90dg Goal Post Corner/Inverted (Apex In)
LB8	Horizontal/Vertical (Tee)
LB8/VD	Straight Length + Face Down
LB8/VU	Straight Length + Face Up
LB8/VDU	Straight Length + Face Down + Face Up
LB9/ATP/A	3 Way Horizontal Corner/L-Hand/With Tower
	Plate
LB9/ATP/B	3 Way Horizontal Corner/R-Hand/With Tower
	Plate
LB9/VD	3 Way Corner + Face Down



30CM SQUARE ALUMINIUM PLATE FEMALE

_B9/VU	3 Way Corner + Face Up
B9/VDU	3 Way Corner + Face Down + Face Up
B10/ATP	4 Way Corner Block With Tower Plate
_B10/VD	4 Way Corner Block + Face Down
_B10/VU	4 Way Corner Block + Face Up
_B10/VDU	4 Way Corner Block + Face Down + Face Up
	Swivel Hinge Frame/Horizontal
BSH/H	
_BSH/V	Swivel Hinge Frame/Vertical
BSC	Swivel Corner Block (Horizontal)
SLICK	LITE BEAM ACCESSORIES
BS/48	Taper Fitting Spacer Female/Male 48mm Long
_BS/75	Taper Fitting Spacer Female/Male 75mm Long
_BS/104	Taper Fitting Spacer Female/Male 104mm Long
ISH/F	Taper Fitting Female To Scaff Clip (Horizontal)
ISH/M	Taper Fitting Male To Scaff Clip (Horizontal)
ISH/M ISV/F	Taper Fitting Female To Scaff Clip (Vertical)
ISV/F ISV/M	
	Taper Fitting Male To Scaff Clip (Vertical)
_BT/F/M12	Taper Fitting Female/M12 Screw On 70mm
ong	
_BT/M/M12	Taper Fitting male/M12 Screw On 70mm Long
_BF/F	Female/Female Sex Changers (Egg Cup)
_BM/M	Male/Male Sex Changers (Egg)
_BSN/F	90dg Truss Snap Connector/Female
_BSN/M	90dg Truss Snap Connector/Male
SLICK	LITE BEAM TOWER PLATES
BTP/S	Aluminum Tower Plate/30cm x 30cm/Scaff
2011/3	Clips
_BTP/S/0	Aluminum Tower Plate/30cm x 30cm/Scaff
10117370	Clips/Opposite
_BTP/C	Aluminum Tower Plate/33.5cm x 33.5cm/U-
DIF/C	Clamps
_BTP/M	Aluminum Tower Plate/30cm x 30cm/No
	Holes/Male
BTP/FM	Aluminum Tower Plate/30cm x 30cm/No
_ВТР/ЕМ	Holes/Female
	hotes/remate
SLICK	LITE BEAM BASE PLATES
STB/M	Steel Base Plate 50cm x 50cm/Male
STB/F	Steel Base Plate 50cm x 50cm/Female
STB/M/Z	Steel Base Plate 50cm x 50cm/Male/Zinc
STB/A/T/M	Aluminum Base Plate/Triangular/Male
STB/A/T/F	Aluminum Base Plate/Triangular/Female
[RP	Taper Pin
R1	R-Clip For Taper Pin
	it oup for idport in