POST OFFICE BOX 5327 - COMPTON, CA 90224 2068 GLADWICK STREET - COMPTON, CA 90220 (310) 537-6996 - (800) 400-0047 - FAX (310) 537-0312 E-Mail: info@innovative-sys.com - Website: www.innovative-sys.com

Engineering Specifications for Innovative Systems Adjustable Upright

Adjustable Uprights are designed to hold a maximum load of 50 lbs between upright, evenly distributed over the 10 foot width crossbar (Telescopic Drape Support). The Adjustable Upright must not be extended beyond the label "Do Not Raise Beyond This Level".

The Recommended Base Plate for Various Adjustable Uprights is listed below. It is always good practice to add additional weight (ie: Sand Bags or weights) on top of the Bases Plates. Especially if heavier drape is used or if traffic is moving about the uprights. One should be particularly careful not to open any large doors in the facility allowing wind force to be applied to your back wall. This can cause the back wall (Uprights) to be blown over.

ADJUSTABLE UPRIGHTS		
2 Piece Adjustable Uprights		
PART#	SIZE	Recommended Base Size
TS35	3' - 5'	B1416 (12 LB)
TS47	4' - 7'	B1416 (12 LB)
TS58	5' ~ 8'	B1416 (12 LB)
TS610	6' - 10'	B1818 (17.5 LB)
TS712	7' - 12'	B1818 (17.5 LB)
TS814	8' - 14'	B181838 (35 LB)
TS916	9' - 16'	B181838 (35 LB)
TS1018	10' - 18'	B2424 (31 LB)
TS1120	11' - 20'	B242438 (62 LB)
TS1222	12' - 22'	B242438 (62 LB)
TS1324	13' - 24'	B242438 (62 LB)
TS1426	14' - 26'	B242438 (62 LB)
Special	Custom Heights Available	
3 Piece Adjustable Uprights		
TS511	5' - 11'	B1818 (17.5 LB)
TS614	6' - 14 '	B181838 (35 LB)
TS717	7' - 17'	B181838 (35 LB)
TS820	8' - 20'	B242438 (62 LB)
TS923	9' - 23'	B242438 (62 LB)
Special	Custom Heights Available	